Part Number: KCDC56-123 GREEN

## Features

- 0.56INCH DIGIT HEIGHT.
- LOW CURRENT OPERATION.
- EXCELLENT CHARACTER APPEARANCE.
- I.C. COMPATIBLE.
- MECHANICALLY RUGGED.
- GRAY FACE,WHITE SEGMENT.
- PACKAGE:200PCS/ REEL.
- MOISTURE SENSITIVITY LEVEL : LEVEL 4.
- RoHS COMPLIANT

## Description

The Green source color devices are made with InGaAlP on GaAs substrate Light Emitting Diode.

## Package Dimensions & Internal Circuit Diagram




Notes:
1. All dimensions are in millimeters (inches), Tolerance is ±0.25(0.01")unless otherwise noted.
2. Specifications are subject to change without notice.
3.The gap between the reflector and PCB shall not exceed 0.25mm.

## Selection Guide

| Part No. | Dice | Lens Type | Iv (ucd) [1] @ 10mA | | Description |
|---|---|---|---|---|---|
| | | | Min. | Typ. | |
| KCDC56-123 | GREEN (InGaAIP) | WHITE DIFFUSED | 8000 | 35500 | Common Cathode, Rt. Hand Decimal. |

Note:
1. Luminous Intensity/ Luminous Flux: +/-15%.

## Electrical / Optical Characteristics at $T_A$=25°C

| Symbol | Parameter | Device | Typ. | Max. | Units | Test Conditions |
|---|---|---|---|---|---|---|
| $\lambda$peak | Peak Wavelength | Green | 574 | | nm | $I_F$=20mA |
| $\lambda$D [1] | Dominant Wavelength | Green | 570 | | nm | $I_F$=20mA |
| $\Delta\lambda$1/2 | Spectral Line Half-width | Green | 20 | | nm | $I_F$=20mA |
| C | Capacitance | Green | 15 | | pF | $V_F$=0V;f=1MHz |
| $V_F$ [2] | Forward Voltage | Green | 2.1 | 2.5 | V | $I_F$=20mA |
| $I_R$ | Reverse Current | Green | | 10 | uA | $V_R$ = 5V |

Notes:
1. Wavelength: +/-1nm.
2. Forward Voltage: +/-0.1V.

## Absolute Maximum Ratings at $T_A$=25°C

| Parameter | Green | Units |
|---|---|---|
| Power dissipation | 75 | mW |
| DC Forward Current | 30 | mA |
| Peak Forward Current [1] | 150 | mA |
| Reverse Voltage | 5 | V |
| Operating/Storage Temperature | -40°C To +85°C | |

Note:
1. 1/10 Duty Cycle, 0.1ms Pulse Width.




RELATIVE INTENSITY Vs. WAVELENGTH

**Green** **KCDC56-123**




FORWARD CURRENT Vs FORWARD VOLTAGE




LUMINOUS INTENSITY Vs. FORWARD CURRENT




FORWARD CURRENT DERATING CURVE




LUMINOUS INTENSITY Vs. AMBIENT TEMPERATURE

**KCDC56-123**

Reflow Soldering Profile For Lead-free SMT Process.




NOTES:

1. We recommend the reflow temperature 245°C(+/−5°C).The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

**Recommended Soldering Pattern**
**(Units : mm; Tolerance: ±0.15)**




**Tape Specifications**
**(Units : mm)**