



PRELIMINARY

Product Data Brief / TNY-A9260-C0X

Specification

Processor	ATMEL AT91SAM9260 @ 180MHz
Memory	256Mbytes NAND flash, 8 Bit wide
	64Mbytes SDRAM, 32 Bit wide
	64Kbits serial SPI EEPROM
Setup / Debug	1x USB device & 1x serial port (DBGU or DaughterBoard)
Expansion	1x 50 pins connector (I2C, SPI, USART, SSC, MCI, ISI, TC)
	1x 60 pins connector (USB host, RMII, I2C, USART)
Bootloader	U-Boot
OS	Linux 2.6

Mechanical and environmental

Board size	41 x 36 mm
Power supply voltage	+5V +/-5%
Power requirement	2.5W max (300mA Core , 200mA available for Expansion connectors)
Temperature	0° to 70°C standard (operating), -40° to 85°C (storage)
Humidity	5% to 95% relative humidity, non condensing
Weight	30 grs

Ordering Information

Reference	Part Number	Description
TNY-A9260-C0X	905-00011-A0X	256Mbytes NAND, 64Mbytes SDRAM, 64Kbits EEPROM, Full Option, 0 to 70°C

Notice : The products specifications provided in this datasheet are subject to change without notice.

© 2007 CALAO Systems – All Rights Reserved.

The CALAO Systems logo is a registered trademark of CALAO Systems.

All others names are the property of their respective owners.