DATASHEET 1IPSE1S17-60


DIGITAL HIGH POWER IGBT GATE DRIVER

Main Features

- Single channel for dual- and multilevel topology
- Smart switching with variable gate resistors
- Tuned according to the application
- Reliable protection against
  - over-current in all short circuit conditions
  - over-voltage during turn-off
- Advanced control and protection functions
  - four level desaturation monitoring
  - two level di/dt monitoring
  - feedback clamping with active function
  - multiple soft shut down
  - supply voltage monitoring
  - digital input filter for switching signals
- DC/DC converter included
- Screw connection with high power IGBT modules (base plate 130x140mm or 190x140mm)



Mechanical Dimensions



DATASHEET 1IPSE1S17-60

Key Data

Parameter	*Symbol*	*Value (at +25°C)*
Max. collector-emitter voltage	V_{CE}	1700V
Input supply voltage range	V_{DC}	+14 to +30V
Output voltage: ON/OFF voltage	V_{ON}/V_{OFF}	±15V
Isolation testing voltage (V_{AC} RMS 50Hz / 1 min)	V_{ISOL}	6000V
Switching frequency (max.)	$f_{S\ max}$	120kHz
Peak output current	I_G	±70A
Peak output power	$P_{DC/DC}$	4W
Quiescent current typically	I_{DC}	0.25A (at 15V)
Max. input current at max. load	$I_{DC\ max}$	0.50A (at 15V)
Coupling capacitance primary / secondary side	C_{io}	typ. 1pF, max. 2pF
Switching frequency of isolated converter	$f_{SMPC\ max}$	0.5MHz
Creepage distance		>30mm
Frequency of logic controller	f	20MHz
Operating temperature (measured close to driver surface)	T_{OP}	-40 to +85°C
Storage temperature	T_{ST}	-40 to +85°C
Input driving and output error signal	optical	660nm
Turn-on delay time	t_{pdON}	400nsec
Turn-off delay time	t_{pdOFF}	400nsec
Typical time of soft shut down	t_{SSD}	1-2µsec
Max. system time between fault detection and error notification	t_{SYS}	100nsec
Time between detection of desaturation and gate voltage falling edge	t_{pDES}	300nsec

Interfaces

Interface	*Part Type*	*Remarks*
Optical Receiver	HFBR-2531Z (Avago)	For suitable connectors see www.avagotech.com
Optical Transmitter	HFBR-1531Z (Avago)	
DC supply on PCB	FKC 2,5/2-STF-5,08 (Phoenix)	Connector: 1 x MSTBV 2,5/2-GF-5,08 (part no. 1777073) (Phoenix)

Connections

For the connection between DC/DC converter and the driver board as well as for the power emitter connection we recommend normal cable as short as possible.