
BROADCOM®

Data Sheet

AFBR-POCxxxL

Optical Power Converter



Description

AFBR-POCxxxL belongs to the Broadcom® Power Components product family and converts optical power to electrical power for applications requiring complete electrical isolation in highly demanding industrial environments and applications. AFBR-POCxxxL is an excellent choice for powering electronic circuitry where electrical-wired solutions are not feasible due to high voltage, electromagnetic inductance, or strong magnetic fields.

AFBR-POCxxxL is a multi-junction compound semiconductor device that provides operating voltages for typical 3 VDC or 5 VDC applications, depending on the chip structure selected.

Typically 600 mW of electrical power can be supplied by converting 1.5W (CW) of optical input power over an operating temperature range from –40°C to +85°C.

Smart thermal design simplifies system integration.

AFBR-POCxxxL is optimized for the efficient coupling of MM fibers with commonly available NA. All products are available with industry-standard ST or FC connectors.

The AFBR-POCx04L optical power converters provide a typical output voltage level of 3.7V supporting most 3 VDC applications. The AFBR-POCx06L parts support most 5 VDC applications by providing a typical electrical output voltage level of 5.6V.

Features

- RoHS-compliant
- Fully isolated Power over Fiber (PoF) solution that efficiently converts optical power to electrical power
- Different converter output characteristics are available for a perfect match with target applications
- Supplies typically 600 mW of electrical power
- Operating temperature range of –40°C to +85°C
- Available with threaded ST and FC ports for MM fibers
- Easy heat sink mounting for thermal control
- Threaded ST port for easy panel mount

Applications

Optical power converters can power devices, such as:

- High voltage current sensors and transducers
- E-field and H-field probes
- MRI/RF imaging coils and patient monitoring equipment
- Power conditioning circuitry
- Wireless transmitters
- Aircraft sensors and transducers

Available Options

3 VDC application; ST Port	AFBR-POC404L
3 VDC application; FC Port	AFBR-POC204L
5 VDC application; ST Port	AFBR-POC406L
5 VDC application; FC Port	AFBR-POC206L

Package

The RoHS-compliant compact optical power converters are provided in solid metal housings.

Variants can be ordered with a threaded ST or FC port protected by port caps.

Handling and Design Information

CAUTION! The small junction size inherent in the design of these components increases the components' susceptibility to damage from electrostatic discharge (ESD). Implement advanced static precautions in handling and assembling these components to prevent damage, degradation, or both that may be induced by ESD.

When soldering, it is advisable to leave the protective port cap on the unit to prevent dirt buildup in the fiber or optical assemblies. Good system performance requires clean port optics and cable ferrules to avoid obstructing the optical path.


The optic components are hermetically sealed in a TO header with a glass window. Any dirt particles in the optical path could reduce the conversion efficiency.


AFBR-POCxxxL are photovoltaic devices.

Do not apply an external voltage to the device.

Mechanical Dimensions – ST Port

AFBR-POC4xxL







Dimensions are in mm.

Mechanical Dimensions – FC Port

AFBR-POC2xxL





Dimensions are in mm.

Regulatory Compliance

Feature	Test Method	Performance
Electrostatic Discharge (ESD) to the Electrical Pins Human Body Model	ESDA/JEDEC – JS-001-2017	Min. ± 100V

CAUTION! The small junction size inherent in the design of these components increases the components' susceptibility to damage from electrostatic discharge (ESD). Implement advanced static precautions in handling and assembling these components to prevent damage, degradation, or both that may be induced by ESD.

Process Compatibility

Parameter	Symbol	Minimum	Typical	Maximum	Units
Solder Environment[a,b]	T_{SOLD}	—	—	260	°C
	t_{SOLD}	—	—	10	seconds


a. Maximum temperature refers to peak temperature.

b. Maximum time refers to time spent at peak temperature.

Pin Description

The anode pin side is marked with "+"; the cathode pin side is marked with "–" on the housing.

Figure 1: Polarity of AFBR-POCxxxL Devices



Details about AFBR-POCxxxL

- **AFBR-POCxxxL is a photovoltaic device.**

  The device is a multi-junction compound semiconductor, which works as a power source without any applied external bias while providing electrical power to a load when illuminated. Unlike a standard photovoltaic device, such as a solar cell that is a large semiconductor pn-junction, the power converter is small. Typically, the device is illuminated by light emanating from an optical fiber; therefore, the light is highly concentrated. The AFBR-POCxxxL device is uniquely designed to handle concentrated light levels, which helps to maintain high output of both voltage and current.
- **Never apply an external voltage to the device.**
- **The "+" marking on the housing stands for anode; the "–" for cathode.**

  The markings also indicate the current flow from "+" to" –", when a load is connected to the pins and light is coupled into the device.

  AFBR-POCxxxL devices operate without applying additional external voltage.
- **Use of voltage regulators is recommended for a stable, efficient, and controlled power extraction from AFBR-POCxxxL devices.**

  Typically, photovoltaic devices, such as solar cells, do not have a continuous operating point and for optimum performance, the load must be adjusted accordingly. This adjustment is primarily due to the influence of the optical input power to the device output. Therefore, a fixed load power extraction is not an optimum method for power harvesting with solar cells.

  Conversely, the Broadcom optical power converters operate with controllable laser light coupled into optical fiber, which results in stabilized output of the AFBR-POCxxxL device. For most applications, combining the device with a voltage regulator, such as a DC/DC converter, is sufficient. Integration of ICs providing automatic maximum power point tracking (MPPT) can be done but is typically not needed.

Figure 2: Illustration of a Typical I-V Curve of Optical Power Converters




Figure 2 illustrates the typical output current vs. output voltage characteristics of an optical power converter.

At short circuit, the current output is at its maximum, but no power is delivered. At open circuit, the voltage is at its maximum; however, no power can be extracted. In between, a maximum power point exists, which is the product of the current and the voltage at that specific point. In an ideal application, the load would be tailored to that maximum power point.

Absolute Maximum Ratings

Absolute maximum ratings are those values beyond which damage to the device may occur if these limits are exceeded for other than a short period of time.

Parameter	Symbol	Min.	Typ.	Max.	Units
Storage Temperature	T_S	–40	—	85	°C
Operating Case Temperature	T_C	–40	—	85	°C
Relative Humidity	RH	5	—	95	%
Optical Input Power Range[a]	$P_{opt\ IN}$	—	—	1.5	W

a. Optical input power (808 nm, continuous wave) at the end of a short connectorized MM fiber measured with an optical power meter.

Fiber Specifications

Protect connectorized fiber by a sleeve or a ceramic ferrule during handling.

Parameter	Symbol	Min.	Typ.	Max.	Units
Core Diameter[a]	D	—	62.5	—	µm
Numeric Aperture	NA	0.22	0.275	0.375	
Fiber Length[b]	—	—	Application specific	—	meter

a. The minimum and maximum fiber core diameter that can be used with AFBR-POCxxxL products is related to the fiber-specific numerical aperture value.Typically fibers with core diameter from 50 µm to 200 µm match with the specified NA range (0.22 to 0.375). For highest energy conversion efficiency fibers with NA from 0.22 to 0.28 are recommended.

b. Fiber length depends on application requirements, mainly depending on fiber attenuation. Exemplarily a typical GI-MM 62.5 µm/125 µm fiber has an attenuation of around 3.5 dB/km at 830 nm.

AFBR-POCx04L

Optical power converters provide electrical output voltage levels for most 3 VDC applications.

Operating Characteristics

All specified parameters are valid for operations at 25°C case temperature and the use of a thermal interface material rated for a thermal contact resistance of less than 1.3 cm^2K/W.

Parameter	Symbol	Min.	Typ.	Max.	Units
Response optical spectrum range[a]	λ_{IN}	800	808	850	nm
Maximum Electrical Output Power vs. optical input power[b]	P_{out} at 0.5 $W_{opt\ IN}$	—	200	—	mW
	P_{out} at 1.0 $W_{opt\ IN}$	—	450	—	
	P_{out} at 1.5 $W_{opt\ IN}$	—	600	—	
Output Voltage at maximum electrical output power	V_{out} at 0.5 $W_{opt\ IN}$	—	3.6	—	V
	V_{out} at 1.0 $W_{opt\ IN}$	—	3.7	—	
	V_{out} at 1.5 $W_{opt\ IN}$	—	3.8	—	
Output Current at maximum electrical output power	I_{out} at 0.5 $W_{opt\ IN}$	—	60	—	mA
	I_{out} at 1.0 $W_{opt\ IN}$	—	120	—	
	I_{out} at 1.5 $W_{opt\ IN}$	—	170	—	

a. For operations over temperature laser light with a wavelength not exceeding 830 nm is recommended.

b. Optical input power (808 nm, continuous wave) at the end of a short connectorized MM fiber measured with an optical power meter. Valid for multimode fibers with NA from 0.22 to 0.28.

The product characteristic diagrams (Figure 3 through Figure 8) are based on measurements of an AFBR-POCx04L with a laser emitting at 808 nm for optical input powers up to 1.5W.

Figure 3: Output I-V Curves at –40°C; 1 × AFBR-POCx04L




Figure 4: Output I-V Curves at 25°C; 1 × AFBR-POCx04L




Figure 5: Output I-V Curves at +85°C; 1 × AFBR-POCx04L




Figure 6: Electrical Output Power; 1 × AFBR-POCx04L




Figure 7: Efficiency; 1 × AFBR-POCx04L





Figure 8: Output Voltage vs. Temperature; 1 × AFBR-POCx04L



AFBR-POCx06L

Optical power converters provide electrical output voltage levels for most 5 VDC applications.

Operating Characteristics

All specified parameters are valid for operations at 25°C case temperature and the use of a thermal interface material rated for a thermal contact resistance of less than 1.3 cm^2K/W.

Parameter	Symbol	Min.	Typ.	Max.	Units
Response Optical Spectrum Range[a]	λ_{IN}	800	808	850	nm
Maximum Electrical Output Power vs. optical input power[b]	P_{out} at 0.5 $W_{opt\ IN}$	—	200	—	mW
	P_{out} at 1.0 $W_{opt\ IN}$	—	450	—	
	P_{out} at 1.5 $W_{opt\ IN}$	—	600	—	
Output Voltage at maximum electrical output power	V_{out} at 0.5 $W_{opt\ IN}$	—	5.4	—	V
	V_{out} at 1.0 $W_{opt\ IN}$	—	5.6	—	
	V_{out} at 1.5 $W_{opt\ IN}$	—	5.7	—	
Output Current at maximum electrical output power	I_{out} at 0.5 $W_{opt\ IN}$	—	36	—	mA
	I_{out} at 1.0 $W_{opt\ IN}$	—	72	—	
	I_{out} at 1.5 $W_{opt\ IN}$	—	108	—	

a. For operations over temperature laser light with a wavelength not exceeding 830 nm is recommended.

b. Optical input power (808 nm, continuous) at the end of a short connectorized MM fiber measured with an optical power meter. Valid for multimode fibers with NA from 0.22 to 0.28.

The product characteristic diagrams (Figure 9 through Figure 14) are based on measurements of an AFBR-POCx06L with a laser emitting at 808 nm for optical input powers up to 1.5W.

Figure 9: Output I-V Curves at –40°C; 1 × AFBR-POCx06L




Figure 10: Output I-V Curves at 25°C; 1 × AFBR-POCx06L




Figure 11: Output I-V Curves at 85°C; 1 × AFBR-POCx06L




Figure 12: Electrical Output Power; 1 x AFBR-POCx06L




Figure 13: Efficiency; 1 × AFBR-POCx06L





Figure 14: Output Voltage vs. Temperature; 1 × AFBR-POCx06L



Broadcom, the pulse logo, Connecting everything, Avago Technologies, Avago, and the A logo are among the trademarks of Broadcom and/or its affiliates in the United States, certain other countries and/or the EU.

Copyright © 2017 by Broadcom. All Rights Reserved.

The term “Broadcom” refers to Broadcom Limited and/or its subsidiaries. For more information, please visit www.broadcom.com.

Broadcom reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. Information furnished by Broadcom is believed to be accurate and reliable. However, Broadcom does not assume any liability arising out of the application or use of this information, nor the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

BROADCOM®

Lead (Pb) Free
RoHS 6 fully
compliant