


# PRODUCT SPECIFICATION


DATE:08/28/2002

<b>COSMO</b> ELECTRONICS CORPORATION	PHOTO <sup>E</sup> MOS RELAYS: <b>KAQV414S</b>	NO. 62M11002 SHEET 1 OF 7	REV. 1
---	---	------------------------------	-----------

- OUTSIDE DIMENSION :



- Operate/Reverse time



## Absolute Maximum Ratings ( $T_A = 25^\circ C$ )

### Emitter (Input)

Reverse Voltage . . . . . 5.0V  
Continuous Forward Current . . . . . 50mA  
Peak Forward Current (1s) . . . . . 1A  
Power Dissipation. . . . . 100mW  
Derate Linearly from  $25^\circ C$  . . . . .  $1.3mW/^\circ C$

### Detector (Output)

Output Breakdown Voltage . . . . .  $\pm 400V$   
Continous Load Current . . . . .  $\pm 130mA$   
Power Dissipation . . . . . 500mW

### General Characteristics

Isolation Test Voltage. . . . . 1500VAC<sub>RMS</sub>  
Isolation Resistance  
 $V_{IO} = 500V, T_A = 25^\circ C$  . . . . .  $> 10^{10} \Omega$   
Total Power Dissipation . . . . . 550mW

Derate Linearly form  $25^\circ C$  . . . . .  $2.5mW/^\circ C$

Storage Temperature Range . . . . . -40 to  $+150^\circ C$

Operating Temperature Range. . . . . -40 to  $+85^\circ C$

Junction Temperature . . . . .  $100^\circ C$

Soldering Temperature, 2mm from case, 10 sec.  $260^\circ C$

# PRODUCT SPECIFICATION

DATE: 08/28/2002

COSMO ELECTRONICS CORPORATION	PHOTO <sup>E</sup> MOS RELAYS: <b>KAQV414S</b>	NO. 62M11002	REV. 1
		SHEET 2 OF 7	

## Characteristics

( $T_A = 25^\circ C$ )

Description	Symbol	Min.	Typ.	Max.	Unit	Test Condition
<b>Emitter (Input)</b>						
Forward Voltage	$V_F$		1.2	1.5	V	$I_F = 10mA$
Operation Input Current	$I_{F OFF}$			5	mA	$V_L = \pm 20V, I_L = < 5\mu A$
Recovery Input Current	$I_{F ON}$	0.2			mA	$V_L = \pm 20V, I_L = 100mA$ $t = 10 ms$
<b>Deterctor (Output)</b>						
Output Breakdown Voltage	$V_B$	400			V	$I_B = 50\mu A$
Output Off-State Leakage	$I_{T OFF}$		0.2	1	$\mu A$	$V_T = 100V, I_F = 10mA$
I/O Capacitance	$C_{ISO}$		6		pF	$I_F = 0, f = 1MHz$
ON Resistance Connection	A	$R_{ON}$	25	50	$\Omega$	$I_L = 100mA, I_F = 0mA$
	B		14	25		
	C		7	12.5		
Reverse(ON) Time	$T_{ON}$		0.6	1.5	ms	$I_F = 10mA, V_L = \pm 20V$ $t = 10ms, I_L = \pm 100mA$
Operate(OFF) Time	$T_{OFF}$		0.3	1.0	ms	

Mos Relay Schematic and Wiring Diagrams						
Type	Schematic	Output configuration	Load	Con-nection	Wiring diagram	
KAQV414S		AC/DC 1b	A DC	A B C		


# PRODUCT SPECIFICATION

DATE:08/28/2002


COSMO ELECTRONICS CORPORATION	PHOTO <sup>E</sup> MOS RELAYS: <b>KAQV414S</b>	NO. 62M11002	REV.
		SHEET 3 OF 7	1

## DATA CURVE


Load current vs. ambient temperature  
Allowable ambient temperature:  
-40° C+85° C




On resistance vs. ambient temperature  
Across terminals 4 and 6 pin  
LED current: 5mA  
Continuous load current: 130 mA(DC)



Operate(OFF) time vs. ambient temperature  
Load voltage 400 V(DC)  
LED current :5mA  
Continuous load current: 130mA(DC)



Reverse(ON) time vs. ambient temperature  
LED current: 5mA; Load voltage: 400V(DC)  
Continuous load current: 130mA(DC)




# PRODUCT SPECIFICATION

DATE: 08/28/2002

<b>COSMO</b> ELECTRONICS CORPORATION	PHOTO <sup>E</sup> MOS RELAYS: <b>KAQV414S</b>	NO. 62M11002 SHEET 4 OF 7	REV. 1
---	---	------------------------------	-----------


LED operate(OFF) vs. ambient temperature  
Load voltage: 400V(DC)

Continuous load current: 130mA(DC)




LED reverse(ON) current vs. ambient temperature  
Load voltage: 400V(DC)

Continuous load current: 130mA(DC)



LED dropout voltage vs. ambient temperature


LED current: 5 to 50mA



Voltage vs. current characteristics of output at MOS FET portion

Measured portion: across terminals 4 and 6 pin

Ambient temperature: 25°C




# PRODUCT SPECIFICATION


DATE:08/28/2002

COSMO ELECTRONICS CORPORATION	PHOTO E <sup>M</sup> S RELAYS: <b>KAQV414S</b>	NO. 62M11002	REV. 1
SHEET 5 OF 7			


LED forward current vs. Operate(OFF) time  
Across terminals 4 and 6pin;Load voltage:  
400V(DC);Continuous load current:130mA(DC)  
;Ambient temperature: 25° C




Off state leakage current  
Across terminals 4 and 6pin  
Ambient temperature: 25° C



LED forward current vs. reverse(ON) time  
Across terminals 4 and 6pin;Load voltage: 400V(DC);Continuous load current: 130 mA(DC);Ambient temperature: 25° C



Applied voltage vs. output capacitance  
Across terminals 4 and 6pin  
Frequency: 1MHz;Ambient temperature:  
25° C




# PRODUCT SPECIFICATION

DATE:08/28/2002

COSMO ELECTRONICS CORPORATION	PHOTO MOS RELAYS: <b>KAQV414S</b>	NO. 62M11002 SHEET 6 OF 7	REV. 1
----------------------------------	--------------------------------------	------------------------------	-----------


## USING METHODS

Examples of resistance value to control LED forward current  $I_F$



E	R
3.3V	Approx. 330 ohm
5V	Approx. 640 ohm
12V	Approx. 1.9K ohm
15V	Approx. 2.5K ohm
24V	Approx. 4.1K ohm

- (1) LED forward current must be more than 5mA, at E min.
- (2) LED forward current must be less than 50mA, at E max.





# PRODUCT SPECIFICATION

DATE: 08/28/2002

COSMO ELECTRONICS CORPORATION	PHOTO MOS RELAYS: KAQV414S	NO. 62M11002	REV.
		SHEET 7 OF 7	1

## USING METHODS

Regulate the spike voltage generated on the inductive load as follows



R-C Snubber