

16-BIT, LOW POWER, VOLTAGE OUTPUT, I²C INTERFACE DIGITAL-TO-ANALOG CONVERTER

FEATURES

- **Micropower Operation: 160 μ A @ 5 V**
- **Power-On Reset to Zero**
- **Single Supply: +2.7 V to +5.5 V**
- **16-Bit Monotonic**
- **Settling Time: 10 μ s to \pm 0.003% FSR**
- **I²C™ Interface With High-Speed Mode**
- **Supports Data Receive and Transmit**
- **On-Chip Rail-to-Rail Output Buffer**
- **Double-Buffered Input Register**
- **Supports Synchronous Multichannel Update**
- **Offset Error: \pm 1 mV max at 25°C**
- **Full-Scale Error: \pm 3 mV max at 25°C**
- **Small 8 Lead MSOP Package**

APPLICATIONS

- **Process Control**
- **Data Acquisition Systems**
- **Closed-Loop Servo Control**
- **PC Peripherals**
- **Portable Instrumentation**


DESCRIPTION

The DAC8571 is a small low-power, 16-bit voltage output DAC with an I²C compatible two-wire serial interface. Its on-chip precision output amplifier allows rail-to-rail output swing and settles within 10 microseconds. The DAC8571 architecture is 16-bit monotonic, and factory trimming typically achieves \pm 4 mV absolute accuracy at all codes. The DAC8571 requires an external reference voltage to set its output voltage range.

The low power consumption and small size of this part make it ideally suited to portable battery operated equipment. The power consumption is typically 800 μ W at V_{DD} = 5 V reducing to 1 μ W in power-down mode.

The DAC8571 incorporates a 2-wire I²C interface. Standard, fast, and high-speed modes of I²C operation are all supported up to 3.4 MHz serial clock speeds. Multichannel synchronous data update and power-down operations are supported through the I²C bus. DAC8571 is also capable of transmitting the contents of its serial shift register, a key feature for I²C system verification.

The DAC8571 is available in an 8-lead MSOP package and is specified over -40°C to 105°C.




Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

I²C is a trademark of Philips Corporation.



These devices have limited built-in ESD protection. The leads should be shorted together or the device placed in conductive foam during storage or handling to prevent electrostatic damage to the MOS gates.



PIN DESCRIPTION

| Pin | Name | Function |
|-----|----------------------|--|
| 1 | V _{DD} | Analog voltage supply input |
| 2 | V _{REF} | Positive reference voltage input |
| 3 | V _(SENSE) | Analog output sense |
| 4 | V _{OUT} | Analog output voltage from DAC |
| 5 | A0 | Device address select |
| 6 | SCL | Serial clock input |
| 7 | SDA | Serial data input/output |
| 8 | GND | Ground reference point for all circuitry on the part |

PACKAGE/ORDERING INFORMATION

| Product | Package | Package Designator | Specified Temperature Range | Package Marking | Ordering Number | Transport Media, Quantity |
|---------|---------|--------------------|-----------------------------|-----------------|-----------------------------|----------------------------------|
| DAC8571 | 8-MSOP | DGK | -40°C to +105°C | D871 | DAC8571IDGK DAC8571IDGKR | Tube, 80 Tape & Reel, 2500 |

ABSOLUTE MAXIMUM RATINGS⁽¹⁾

| | UNITS | |
|--|----------------------------------|-------|
| V _{DD} to GND | -0.3 V to +6 V | |
| Digital input voltage to GND | -0.3V to V _{DD} + 0.3V | |
| V _{OUT} to GND | -0.3V to +V _{DD} + 0.3V | |
| Operating temperature range | -40°C to + 105°C | |
| Storage temperature range | -65°C to +150°C | |
| Junction temperature range (T _{J,max}) | + 150°C | |
| Θ _{JA} Thermal impedance | 260°C/W | |
| Θ _{JC} Thermal impedance | 44°C/W | |
| Lead temperature, soldering | Vapor phase (60s) | 215°C |
| | Infrared (15s) | 220°C |

(1) Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. Exposure to absolute maximum conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS
 $V_{DD} = +2.7\text{ V to }+5.5\text{ V}$; $R_L = 2\text{ k}\Omega$ to GND; $C_L = 200\text{ pF}$ to GND; low power mode; all specifications $-40^\circ\text{C to }105^\circ\text{C}$ (unless otherwise noted)

| PARAMETER | CONDITIONS | DAC8571 | | | UNITS |
|---|--|-------------|------------|-------------|------------------------------|
| | | MIN | TYP | MAX | |
| STATIC PERFORMANCE (1) | | | | | |
| Resolution | | 16 | | | Bits |
| Relative accuracy | | | | ± 0.098 | % of FSR |
| Differential nonlinearity | Monotonic by design | | ± 0.25 | ± 1 | LSB |
| Offset error | Measured at code 485, 25°C | | 0.3 | ± 1.0 | mV |
| | Measured at code 485, $-40^\circ\text{C} \dots 105^\circ\text{C}$ | | 1.0 | ± 5.0 | |
| Full-scale error | Measured at code 64714, 25°C | | 0.5 | ± 3.0 | mV |
| | Measured at code 64714, $-40^\circ\text{C} \dots 105^\circ\text{C}$ | | 1.0 | ± 5.0 | |
| Gain error | Measured at code 64714, 25°C | | 1.0 | ± 3.0 | mV |
| | Measured at code 64714, $-40^\circ\text{C} \dots 105^\circ\text{C}$ | | 2.0 | ± 5.0 | |
| Zero code error drift | All zeroes loaded to DAC register | | -20 | | $\mu\text{V}/^\circ\text{C}$ |
| Gain temperature coefficient | | | -5 | | ppm of FSR/ $^\circ\text{C}$ |
| Absolute accuracy | All codes from code 485 to code 64714, 25°C | | ± 2.5 | | mV |
| | All codes from code 485 to code 64714, $-40^\circ\text{C} \dots 105^\circ\text{C}$ | | ± 3.5 | | |
| OUTPUT CHARACTERISTICS (2) | | | | | |
| Output voltage range | | 0 | | V_{REF} | V |
| Output voltage settling time (full scale) | $R_L = 2\text{ k}\Omega$; $C_L < 200\text{ pF}$, fast settling | | 8 | 10 | μs |
| | $R_L = 2\text{ k}\Omega$; $C_L = 500\text{ pF}$, fast settling | | 12 | | μs |
| | $R_L = 2\text{ k}\Omega$; $C_L < 200\text{ pF}$, low power | | 13 | 15 | μs |
| Slew rate | $R_L = 2\text{ k}\Omega$; $C_L < 200\text{ pF}$, fast settling | | 1 | | $\text{V}/\mu\text{s}$ |
| | $R_L = 2\text{ k}\Omega$; $C_L < 200\text{ pF}$, low power | | 0.5 | | |
| Capacitive load stability | $R_L = \infty$ | | 470 | | pF |
| | $R_L = 2\text{ k}\Omega$ | | 1000 | | pF |
| Digital-to-analog glitch impulse | | | 20 | | nV-s |
| Digital feedthrough | | | 0.5 | | nV-s |
| DC output impedance | | | 1 | | Ω |
| Short circuit current | $V_{DD} = +5\text{ V}$ | | 50 | | mA |
| | $V_{DD} = +3\text{ V}$ | | 20 | | mA |
| Power-up time | Coming out of power-down mode, $V_{DD} = +5\text{ V}$ | | 2.5 | | μs |
| | Coming out of power-down mode, $V_{DD} = +3\text{ V}$ | | 5 | | μs |
| PSRR | | | 0.75 | | mV/V |
| REFERENCE INPUT | | | | | |
| V_{REFH} input range | | 0 | | V_{DD} | V |
| Reference input impedance | | | 140 | | k Ω |
| LOGIC INPUTS (2) | | | | | |
| Input current | | | | ± 1 | μA |
| V_{IN_L} , Input low voltage | $V_{DD} = 2.7\text{--}5.5\text{ V}$ | | | $0.3V_{DD}$ | V |
| V_{IN_H0} , Input high voltage | $V_{DD} = 2.7\text{--}5.5\text{ V}$ | $0.7V_{DD}$ | | | V |
| Pin capacitance | | | | 3 | pF |
| POWER REQUIREMENTS | | | | | |
| V_{DD} | | 2.7 | | 5.5 | V |
| I_{DD} (normal operation) | DAC active, I_{ref} included | | | | |

(1) Linearity calculated using a reduced code range of 485 to 64714. Output unloaded.

(2) Assured by design and characterization, not production tested.

ELECTRICAL CHARACTERISTICS (continued)

$V_{DD} = +2.7\text{ V to }+5.5\text{ V}$; $R_L = 2\text{ k}\Omega\text{ to GND}$; $C_L = 200\text{ pF to GND}$; low power mode; all specifications $-40^\circ\text{C to }105^\circ\text{C}$ (unless otherwise noted)

| PARAMETER | CONDITIONS | DAC8571 | | | UNITS |
|---|---|---------|------|-----|---------------|
| | | MIN | TYP | MAX | |
| $V_{DD} = +4.5\text{ V to }+5.5\text{ V}$ | $V_{IH} = V_{DD}$, $V_{IL} = \text{GND}$, fast settling | | 250 | 400 | μA |
| | $V_{IH} = V_{DD}$, $V_{IL} = \text{GND}$, low power | | 160 | 225 | |
| $V_{DD} = +2.7\text{ V to }+3.6\text{ V}$ | $V_{IH} = V_{DD}$, $V_{IL} = \text{GND}$, fast settling | | 240 | 380 | μA |
| | $V_{IH} = V_{DD}$, $V_{IL} = \text{GND}$, low power | | 140 | 200 | |
| I_{DD} (all power-down modes) | DAC active, I_{ref} included | | | | |
| $V_{DD} = +4.5\text{ V to }+5.5\text{ V}$ | $V_{IH} = V_{DD}$ and $V_{IL} = \text{GND}$ | | 0.2 | 1 | μA |
| $V_{DD} = +2.7\text{ V to }+3.6\text{ V}$ | $V_{IH} = V_{DD}$ and $V_{IL} = \text{GND}$ | | 0.05 | 1 | μA |
| POWER EFFICIENCY | | | | | |
| I_{OUT}/I_{DD} | $I_L = 2\text{ mA}$, $V_{DD} = +5\text{ V}$ | | 93% | | |

TIMING CHARACTERISTICS

$V_{DD} = +2.7\text{ V to }+5.5\text{ V}$; $R_L = 2\text{ k}\Omega\text{ to GND}$; all specifications $-40^\circ\text{C to }105^\circ\text{C}$ (unless otherwise noted)

| SYMBOL | PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|----------------------|--|---|---------------|-----|------|---------------|
| t_{SCL} | SCL clock frequency | Standard mode | | | 100 | kHz |
| | | Fast mode | | | 400 | kHz |
| | | High-speed mode, $C_B - 100\text{pF max}$ | | | 3.4 | MHz |
| | | High-speed mode, $C_B - 400\text{pF max}$ | | | 1.7 | MHz |
| t_{BUF} | Bus free time between a STOP and START condition | Standard mode | 4.7 | | | μs |
| | | Fast mode | 1.3 | | | μs |
| t_{HO} ; t_{STA} | Hold time (repeated) START condition | Standard mode | 4.0 | | | μs |
| | | Fast mode | 600 | | | ns |
| | | High-speed mode | 160 | | | ns |
| t_{LOW} | LOW period of the SCL clock | Standard mode | 4.7 | | | μs |
| | | Fast mode | 1.3 | | | μs |
| t_{HIGH} | HIGH period of the SCL clock | Standard mode | 4.0 | | | μs |
| | | Fast mode | 600 | | | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 60 | | | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 120 | | | ns |
| t_{SU} ; t_{STA} | Setup time for a repeated START condition | Standard mode | 4.7 | | | μs |
| | | Fast mode | 600 | | | ns |
| | | High-speed mode | 160 | | | ns |
| t_{SU} ; t_{DAT} | Data setup time | Standard mode | 250 | | | ns |
| | | Fast mode | 100 | | | ns |
| | | High-speed mode | 10 | | | ns |
| t_{HD} ; t_{DAT} | Data hold time | Standard mode | 0 | | 0.9 | μs |
| | | Fast mode | 0 | | 0.9 | μs |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 0 | | 70 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 0 | | 150 | ns |
| t_{RCL} | Rise time of SCL signal | Standard mode | $20 + 0.1C_B$ | | 1000 | ns |
| | | Fast mode | $20 + 0.1C_B$ | | 300 | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 10 | | 40 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 20 | | 80 | ns |

TIMING CHARACTERISTICS (continued)
 $V_{DD} = +2.7\text{ V to }+5.5\text{ V}$; $R_L = 2\text{ k}\Omega$ to GND; all specifications $-40^\circ\text{C to }105^\circ\text{C}$ (unless otherwise noted)

| SYMBOL | PARAMETER | TEST CONDITIONS | MIN | TYP | MAX | UNITS |
|-------------------|--|---|---------------|-----|------|---------------|
| t_{RCL1} | Rise time of SCL signal after a repeated START condition, and after an acknowledge BIT | Standard mode | $20 + 0.1C_B$ | | 1000 | ns |
| | | Fast mode | $20 + 0.1C_B$ | | 300 | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 10 | | 80 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 20 | | 1600 | ns |
| t_{FCL} | Fall time of SCL signal | Standard mode | $20 + 0.1C_B$ | | 300 | ns |
| | | Fast mode | $20 + 0.1C_B$ | | 300 | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 10 | | 40 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 20 | | 80 | ns |
| t_{RCA} | Rise time of SDA signal | Standard mode | $20 + 0.1C_B$ | | 1000 | ns |
| | | Fast mode | $20 + 0.1C_B$ | | 300 | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 10 | | 80 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 20 | | 160 | ns |
| t_{FDA} | Fall time of SDA signal | Standard mode | $20 + 0.1C_B$ | | 300 | ns |
| | | Fast mode | $20 + 0.1C_B$ | | 300 | ns |
| | | High-speed mode, $C_B - 100\text{pF max}$ | 10 | | 80 | ns |
| | | High-speed mode, $C_B - 400\text{pF max}$ | 20 | | 160 | ns |
| $t_{SU}; t_{STO}$ | Setup time for STOP condition | Standard mode | 4.0 | | | μs |
| | | Fast mode | 600 | | | ns |
| | | High-speed mode | 160 | | | ns |
| C_B | Capacitive load for SDA and SCL | | | | 400 | pF |
| t_{SP} | Pulse width of spike suppressed | Fast mode | | | 50 | ns |
| | | High-speed mode | | | 10 | ns |
| V_{NH} | Noise margin at the HIGH level for each connected device (including hysteresis) | Standard mode | $0.2V_{DO}$ | | | V |
| | | Fast mode | | | | |
| | | High-speed mode | | | | |
| V_{NL} | Noise margin at the LOW level for each connected device (including hysteresis) | Standard mode | $0.1V_{DO}$ | | | V |
| | | Fast mode | | | | |
| | | High-speed mode | | | | |

TYPICAL CHARACTERISTICS

At $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 1.




Figure 2.




Figure 3.




Figure 4.




Figure 5.




Figure 6.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 7.




Figure 8.




Figure 9.




Figure 10.




Figure 11.




Figure 12.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 13.




Figure 14.




Figure 15.




Figure 16.




Figure 17.




Figure 18.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 19.




Figure 20.




Figure 21.




Figure 22.




Figure 23.




Figure 24.

TYPICAL CHARACTERISTICS (continued)

At $T_A = +25^\circ\text{C}$, unless otherwise noted.




Figure 25.




Figure 26.

THEORY OF OPERATION

D/A SECTION

The architecture of the DAC8571 consists of a string DAC followed by an output buffer amplifier. Figure 27 shows a block diagram of the DAC architecture.




Figure 27. DAC8571 Architecture

The input coding to the DAC8571 is unsigned binary, which gives the ideal output voltage as:

$$V_{OUT} = V_{REF} \times \frac{D}{65536}$$

where D = decimal equivalent of the binary code that is loaded to the DAC register; it can range from 0 to 65535.

RESISTOR STRING

The resistor string section is shown in Figure 28. It is simply a divide-by-two resistor, followed by a string of resistors, each of value R. The code loaded into the DAC register determines at which node on the string the voltage is tapped off to be fed into the output amplifier by closing one of the switches connecting the string to the amplifier. Because it is a string of resistors, it is assured monotonic.




Figure 28. Resistor String.

THEORY OF OPERATION (continued)

Output Amplifier

The output buffer is a gain-of-2 noninverting amplifier capable of generating rail-to-rail voltages at its output, which gives an output range of 0 V to V_{DD} . It is capable of driving a load of 2 k Ω in parallel with 1000 pF to GND. The source and sink capabilities (fast settling) of the output amplifier can be seen in the typical curves. The slew rate is 1 V/ μ s with a full-scale settling time of 10 μ s with the output loaded. The feedback and gain setting resistors of the amplifier are in the order of 50 k Ω . Their absolute value can be off significantly, but they are matched to within 0.1%.

The inverting input of the output amplifier is brought out to the VSENSE pin, through the feedback resistor. This allows for better accuracy in critical applications by tying the VSENSE point and the amplifier output together directly at the load. Other signal conditioning circuitry may also be connected between these points for specific applications including current sourcing.

I²C Interface

The DAC8571 uses the I²C interface (see I²C-Bus Specification Version 2.1, January 2000, Philips Semiconductor) to receive and transmit digital data. I²C is a 2-wire serial interface that allows multiple devices on the same bus to communicate with each other. The serial bus consists of the serial data (SDA) and serial clock (SCL) lines. Connections to the SDA and SCL lines of the bus are made through open drain IO pins of each device on the bus. Since the devices that connect to the bus have open drain outputs, the bus should include pullup structures. When the bus is not active, both SCL and SDA lines are pulled high by these pullup devices.

The DAC8571 supports the I²C serial bus and data transmission protocol, in all three defined modes: standard (100 Kbps), fast (400 kbps), and high speed (3.4 Mbps).

I²C specification states that the device that controls the message is called a *master*, and the devices that are controlled by the master are *slaves*. The master device generates the SCL signal. A master device also generates special timing conditions (start condition, repeated start condition, and stop condition) on the bus to indicate the start or stop of a data transfer. Device addressing is also done by the master. The master device on an I²C bus is usually a microcontroller or a digital signal processor (DSP). The DAC8571 on the other hand, operates as a slave device on the I²C bus. A slave device acknowledges master's commands and upon master's control, either receives or transmits data.

I²C specification states that a device that sends data onto the bus is defined as a transmitter, and a device receiving data from the bus is defined as a *receiver*. DAC8571 normally operates as a slave receiver. A master device *writes* to DAC8571, a slave receiver. However, if a master device inquires DAC8571 internal register data, DAC8571, operates as a slave transmitter. In this case, the master device *reads* from the DAC8571, a slave transmitter. According to I²C terminology, *read* and *write* are with respect to the master device.

Other than specific timing signals, I²C interface works with serial bytes. At the end of each byte, a 9th clock cycle is used to generate/detect an acknowledge signal. An acknowledge is when the SDA line is pulled low during the high period of 9th clock cycle. A *not-acknowledge* is when SDA line is left high during the high period of the 9th clock cycle.




Figure 29. Valid Data

THEORY OF OPERATION (continued)




Figure 30. Acknowledge on the I²C Bus




Figure 31. Bus Protocol

Master Writing to a Slave Receiver (Standard/Fast Modes)

I²C protocol starts when the bus is idle, that is, when SDA and SCL lines are stable high. The master then pulls the SDA line low while SCL is still high indicating that serial data transfer has started. This is called a *start condition*, and can only be asserted by the master. After the start condition, the master generates the serial clock pulses and puts out an address byte, ADDRESS<7:0>. While generating the bit stream, the master ensures the timing for valid data. For each valid I²C bit, SDA line should remain stable during the entire high period of the SCL line. The address byte consists of 7 address bits (1001100, assuming A0=0) and a direction bit ($R/\overline{W}=0$). After sending the address byte, the master generates a 9th SCL pulse and monitors the state of the SDA line during the high period of this 9th clock cycle. The SDA line being pulled low by a receiver during the high period of 9th clock cycle is called an *acknowledge* signal. If the master receives an acknowledge signal, it knows that a DAC8571 successfully matched the address the master sent. Upon the receipt of this acknowledge, the master knows that the communication link with a DAC8571 has been established and more data could be sent. The master continues by sending a control byte C<7:0>, which sets DAC8571's operation mode. After sending the control byte, the master expects an acknowledge signal. Upon receipt of the acknowledge, the master sends a *most significant byte* M<7:0> that represents the eight most significant bits of DAC8571's 16-bit digital-to-analog conversion data. Upon receipt of the M<7:0>, DAC8571 sends an acknowledge. After receiving the acknowledge, the master sends a *least significant byte* L<7:0> that represents the eight least significant bits of DAC8571's 16-bit conversion data. After receiving the L<7:0>, the DAC8571 sends an acknowledge. At the falling edge of the acknowledge signal following the L<0>, DAC8571 performs a digital to analog conversion. For further DAC updates, the master can keep repeating M<7:0> and L<7:0> sequences, expecting an acknowledge after each byte. After the required number of digital-to-analog conversions is complete, the master can break the communication link with DAC8571 by pulling the SDA line from low to high while SCL line is high. This is called a *stop condition*. A stop condition brings the bus back to idle (SDA and SCL both high). A stop condition indicates that communication with DAC8571 has ended. All devices on the bus including DAC8571 then await a new start condition followed by a matching address byte. DAC8571 stays at its current state upon receipt of a stop condition. Table 1 demonstrates the sequence of events that should occur while a master transmitter is writing to DAC8571.

Table 1. Master Transmitter Writing to Slave Receiver (DAC8571)

| Standard/Fast Mode Write Sequence - Data Input | | | | | | | | | |
|---|--|----------|----------|----------|----------|----------|----------|-------------------|-----------------------------|
| Transmitter | MSB | 6 | 5 | 4 | 3 | 2 | 1 | LSB | Comment |
| Master | Start | | | | | | | | Begin sequence |
| Master | 1 | 0 | 0 | 1 | 1 | A0 | 0 | R/ \overline{W} | Write addressing (LSB=0) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | 0 | 0 | Load 1 | Load 0 | 0 | Brcsel | 0 | PD0 | Control byte (PD0=0) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | D15 | D14 | D13 | D12 | D11 | D10 | D9 | D8 | Writing dataword, high byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Writing dataword, low byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | Stop or Repeated Start ⁽¹⁾⁽²⁾ | | | | | | | | Done |

(1) High byte, low byte sequence can repeat.

(2) Use repeated start to secure bus operation and loop back to the stage of write addressing for next Write.

| Standard/Fast Mode Write Sequence-Power Down Input | | | | | | | | | |
|---|--|----------|----------|----------|----------|----------|----------|-------------------|-----------------------------|
| Transmitter | MSB | 6 | 5 | 4 | 3 | 2 | 1 | LSB | Comment |
| Master | Start | | | | | | | | Begin sequence |
| Master | 1 | 0 | 0 | 1 | 1 | A0 | 0 | R/ \overline{W} | Write addressing (LSB=0) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | 0 | 0 | Load 1 | Load 0 | 0 | Brcsel | 0 | PD0 | Control byte (PD0=1) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | PD1 | PD2 | PD3 | 0 | 0 | 0 | 0 | 0 | Writing dataword, high byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Writing dataword, low byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | Stop or Repeated Start ⁽¹⁾⁽²⁾ | | | | | | | | Done |

(1) High byte, low byte sequence can repeat.

(2) Use repeated start to secure bus operation and loop back to the stage of write addressing for next Write.

Master Reading From a Slave Transmitter (Standard/Fast Modes)

I²C protocol starts when the bus is idle, that is, when SDA and SCL lines are stable high. The master then pulls the SDA line low while SCL is still high indicating that serial data transfer has started. This is called a *start condition*, and can only be asserted by the master. After the start condition, the master generates the serial clock pulses and puts out an address byte, ADDRESS<7:0>. While generating the bit stream, the master ensures the timing for valid data. For each valid I²C bit, SDA line should remain stable during the entire high period of the SCL line. The address byte consists of seven address bits (1001100, assuming A0=0) and a direction bit ($R/\overline{W}=1$). After sending the address byte, the master generates a 9th SCL pulse and monitors the state of the SDA line during the high period of this 9th clock cycle (master leaves the SDA line high). The SDA line being pulled low by a receiver during the high period of 9th clock cycle is called an *acknowledge* signal. If the master receives an acknowledge signal, it knows that a DAC8571 successfully matched the address the master sent. Since the R/\overline{W} bit in the address byte was set, master also knows that DAC8571 is ready to transmit data. Upon the receipt of this acknowledge, the master knows that the communication link with a DAC8571 has been established and more data could be received. The master continues by sending eight clock cycles during which DAC8571 transmits a most significant byte, M<7:0>. If the master detects all bits of the M<7:0> as valid data, it sends an acknowledge signal in the 9th cycle. DAC8571 detects this acknowledge signal and prepares to send more data. Upon the receipt of eight clock cycles from the master, DAC8571 transmits the least significant byte L<7:0>. If the master detects all bits of the L<7:0> as valid data, it sends an acknowledge signal to DAC8571 during the 9th clock cycle. DAC8571 detects this acknowledge signal and prepares to send more data. Upon the receipt of 8 more clock cycles from the master, DAC8571 transmits the control byte C<7:0>. During the 9th clock cycle, the master transmits a not-acknowledge signal to DAC8571 and terminates the sequence with a stop condition, by pulling the SDA line from low to high while clock is high. M<7:0> and L<7:0> data could be either DAC data or could be the data stored in the temporary register. Bits in the C<7:0> reveal this information. Table 2 demonstrates the sequence of events that should occur while a master receiver is reading from DAC8571.

Table 2. Master Receiver Reads From Slave Transmitter (DAC8571)

| Standard/Fast Mode Read Sequence-Data Transmit | | | | | | | | | |
|--|-------------------------|-----|-----|-----|-----|-----|----|------------------|--|
| Transmitter | MSB | 6 | 5 | 4 | 3 | 2 | 1 | LSB | Comment |
| Master | Start | | | | | | | | Begin sequence |
| Master | 1 | 0 | 0 | 1 | 1 | A0 | 0 | R/\overline{W} | Read addressing ($R/\overline{W} = 1$) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| DAC8571 | D15 | D14 | D13 | D12 | D11 | D10 | D9 | D8 | High byte |
| Master | Master Acknowledges | | | | | | | | |
| DAC8571 | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Low byte |
| Master | Master Acknowledges | | | | | | | | |
| DAC8571 | C7 | C6 | C5 | C4 | C3 | C2 | C1 | C0 | Control byte |
| Master | Master Not Acknowledges | | | | | | | | Master signal end of read |
| Master | Stop or Repeated Start | | | | | | | | Done |

Master Writing to a Slave Receiver (High-Speed Mode)

All devices must start operation in standard/fast mode and switch to high-speed mode using a well defined protocol. This is required because high-speed mode requires the on chip filter settings of each I²C device (for SDA and SCL lines) to be switched to support 3.4 Mbps operation. A stop condition always ends the high speed mode and puts all devices back to standard/fast mode.

I²C protocol starts when the bus is idle, that is, when SDA and SCL lines are stable high. The master then pulls the SDA line low while SCL is still high indicating that serial data transfer has started. This is called a *start condition*, and can only be asserted by the master. After the start condition, the master device puts out the high-speed master code 0000 1xxx. No device is allowed to acknowledge the master code, but the devices are required to switch their internal settings to support 3.4 Mbps operation upon the receipt of this code. After the not-acknowledge signal, the master is allowed to operate at high speed. Now at much higher speed, the master generates a repeated start condition. After the start condition, master generates the serial clock pulses and puts out an address byte, ADDRESS<7:0>. While generating the bit stream, the master ensures the timing for valid data. For each valid I²C bit, SDA line should remain stable during the entire high period of the SCL line. The address byte consists of seven address bits and a direction bit ($R/\overline{W}=0$). After sending the address byte, the

master generates a 9th SCL pulse and monitors the state of the SDA line during the high period of this 9th clock cycle (master leaves the SDA line high). The SDA line being pulled low by the receiver during the high period of 9th clock cycle is called an *acknowledge* signal. If the master receives an acknowledge signal, it knows that a DAC8571 successfully matched the address the master sent. Upon the receipt of this acknowledge, the master knows that the high-speed communication link with a DAC8571 has been established and more data could be sent. The master continues by sending a control byte, C<7:0>, which sets DAC8571 operation mode. After sending the control byte, master expects an acknowledge. Upon the receipt of an acknowledge, the master sends a *most significant byte*, M<7:0> that represents the eight most significant bits of DAC8571's 16-bit digital-to-analog conversion data. Upon the receipt of the M<7:0>, DAC8571 sends an acknowledge. After receiving the acknowledge, the master sends a *least significant byte*, L<7:0>, that represents the eight least significant bits of DAC8571's 16-bit conversion data. After receiving the L<7:0>, the DAC8571 sends an acknowledge. At the falling edge of the acknowledge signal following the L<0>, DAC8571 performs a digital to analog conversion, depending on the operational mode. For further DAC updates, the master can keep repeating M<7:0> and L<7:0> sequences, expecting an acknowledge after each byte. After the required number of digital to analog conversions is complete, the master can break the communication link with DAC8571 by pulling the SDA line from low to high while SCL line is high. This is called a *stop condition*. A stop condition brings the bus back to idle (SDA and SCL both high). A stop condition indicates that communication with a device (DAC8571) has ended. All devices on the bus including DAC8571 then await a new start condition followed by a matching address byte. DAC8571 stays at its current state upon the receipt of a stop condition. A stop condition during the high-speed mode also indicates the end of the high-speed mode. Table 3 demonstrates the sequence of events that should occur while a master transmitter is writing to DAC8571 in I²C high-speed mode.

Table 3. Master Transmitter Writes to Slave Receiver in High-Speed Mode

| HS Mode Write Sequence-Data Input | | | | | | | | | |
|-----------------------------------|---------------------------------------|-----|--------|--------|-----|--------|----|--------------|--|
| Transmitter | MSB | 6 | 5 | 4 | 3 | 2 | 1 | LSB | Comment |
| Master | Start | | | | | | | | Begin sequence ⁽¹⁾ |
| Master | 0 | 0 | 0 | 0 | 1 | X | X | X | HS mode master code |
| NONE | Not Acknowledge | | | | | | | | No device may acknowledge HS master code |
| Master | Repeated Start | | | | | | | | |
| Master | 1 | 0 | 0 | 1 | 1 | A0 | 0 | R/ \bar{W} | Write addressing (LSB = 0) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | 0 | 0 | Load 1 | Load 0 | 0 | Brcsel | 0 | PD0 | Control byte (PD0=0) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | D15 | D14 | D13 | D12 | D11 | D10 | D9 | D8 | Writing dataword, high byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Writing dataword, low byte |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| Master | Stop or Repeated Start ⁽²⁾ | | | | | | | | Done |

(1) High-byte, low-byte sequences can repeat

(2) Use repeated start to secure bus operation and loop back to the stage of write addressing for next Write.

Master Receiver Reading From a Slave Transmitter (High-Speed Mode)

I²C protocol starts when the bus is idle, that is, when SDA and SCL lines are stable high. The master then pulls the SDA line low while SCL is still high indicating that serial data transfer has started. This is called a *start condition*, and can only be asserted by the master. After the start condition, the master device puts out the high-speed master code 0000 1xxx. No device is allowed to acknowledge the master code, but the devices are required to switch their internal settings to support 3.4 Mbps operation upon the receipt of this code. After the not-acknowledge signal, the master is allowed to operate at high speed. Now at much higher speed, the master generates a repeated start condition. After the start condition, the master generates the serial clock pulses and puts out an address byte, ADDRESS<7:0>. While generating the bit stream, the master ensures the timing for valid data. For each valid I²C bit, SDA line should remain stable during the entire high period of the SCL line. The address byte consists of seven address bits and a direction bit (R/W=1). After sending the address byte, the master generates a 9th SCL pulse and monitors the state of the SDA line during the high period of this 9th clock cycle (master leaves the SDA line high). The SDA line being pulled low by the receiver during the high period of 9th clock cycle is called an *acknowledge* signal. If the master receives an acknowledge signal, it knows that a DAC8571 successfully matched the address the master sent. Since the R/W bit in the address byte was set, master also knows that DAC8571 is ready to transmit data. Upon the receipt of this acknowledge, the master knows that the communication link with a DAC8571 has been established and more data could be received. The master continues by sending eight clock cycles during which DAC8571 transmits an M<7:0>. If the master detects all bits of the M<7:0> as valid data, it sends an acknowledge signal in the 9th cycle. DAC8571 detects this acknowledge signal and prepares to send more data. Upon the receipt of eight more clock cycles from the master, DAC8571 transmits L<7:0>. If the master detects all bits of the L<7:0> as valid data, it sends an acknowledge signal to DAC8571 during the 9th clock cycle. DAC8571 detects this acknowledge signal and prepares to send more data. Upon the receipt of eight more clock cycles from the master, DAC8571 transmits the control byte, C<7:0>. In the 9th clock cycle the master transmits a not-acknowledge signal to DAC8571 and terminates the sequence with a stop condition, by pulling the SDA line from low to high while clock is high. M<7:0> and L<7:0> data could be either DAC data or could be the data stored in the temporary register. Bits in the C<7:0> reveal this information. A stop condition during the high-speed mode also indicates the end of the high-speed mode. Table 4 demonstrates the sequence of events that should occur while a master receiver is reading from DAC8571 in I²C high-speed mode.

Table 4. Master Receiver Reads Data From Slave Transmitter in High-Speed Mode

| HS Mode Read Sequence-Data Transmit | | | | | | | | | |
|-------------------------------------|---------------------------------------|-----|-----|-----|-----|-----|----|-----|--|
| Transmitter | MSB | 6 | 5 | 4 | 3 | 2 | 1 | LSB | Comment |
| Master | Start | | | | | | | | Begin sequence |
| Master | 0 | 0 | 0 | 0 | 1 | X | X | X | HS Mode master code |
| NONE | Not Acknowledge | | | | | | | | No device may acknowledge HS master code |
| Master | Repeated Start | | | | | | | | |
| Master | 1 | 0 | 0 | 1 | 1 | A0 | 0 | R/W | Read addressing (R/W=1) |
| DAC8571 | DAC8571 Acknowledges | | | | | | | | |
| DAC8571 | D15 | D14 | D13 | D12 | D11 | D10 | D9 | D8 | High byte |
| Master | Master Acknowledges | | | | | | | | |
| DAC8571 | D7 | D6 | D5 | D4 | D3 | D2 | D1 | D0 | Low byte |
| Master | Master Acknowledges | | | | | | | | |
| DAC8571 | C7 | C6 | C5 | C4 | C3 | C2 | C1 | C0 | Control byte |
| Master | Master Not Acknowledges | | | | | | | | Master signal end of read |
| Master | Stop or Repeated Start ⁽¹⁾ | | | | | | | | Done |

(1) Use repeated start to secure bus operation and loop back to the stage of write addressing for next Write.

DAC8571 Update Sequence

DAC8571 requires a start condition, a valid I²C address, a control byte, an MS byte and an LS byte for an update. The control byte sets the operational mode of the DAC8571. After the receipt of the control byte, DAC8571 expects an MS byte and an LS byte. After the receipt of each byte, DAC8571 acknowledges by pulling the SDA line low. At the falling edge of the acknowledge signal that follows the LS byte, DAC8571 performs an update.

After the first update, further data can be sent as MS byte and LS byte sequences and DAC8571 keeps updating at the falling edge of the acknowledge signal that follows each LS byte. The bits of the last control byte determine the type of update being performed. Thus, for the first update, DAC8571 requires a start condition, a valid I²C address, a control byte, an MS byte and an LS byte. For all consecutive updates, DAC8571 needs an MS byte and an LS byte.

Using the I²C high-speed mode, the clock running a 3.4 MHz, each 16-bit DAC update can be done within 18-clock cycles (MS byte, acknowledge bit, LS byte, acknowledge bit), at 188.88 KSPS. Using the fast mode, clock running at 400 kHz, maximum DAC update rate is limited to 22.22 KSPS.

DAC8571 Address Byte

| MSB | | | | | | LSB |
|-----|---|---|---|---|----|-----|
| 1 | 0 | 0 | 1 | 1 | A0 | 0 |
| | | | | | | R/W |

The address byte is the first byte received following a START condition from the master device. The first five bits (MSBs) of the slave address are factory preset to 10011. The next bit of the address byte is the device select bit A0, followed by a fixed 0 and the read/write direction bit R/W. In order for DAC8571 to respond, the 7-bit address should be 10011A00, where the state of the A0 bit matches the state of the A0 pin. A maximum of two DAC8571 devices with the same preset code can therefore be connected on the same bus at one time. The A0 Address inputs can be permanently connected to VDD or digital ground, or can be actively driven by TTL or CMOS logic levels. The device address is set by the state of these pins upon power up of the DAC8571. The last bit of the address byte (R/W) defines the direction of the data flow. When set to a 1, a read operation is selected (master device reads from DAC8571); when set to a 0, a write operation is selected (master device writes to DAC8571). Following the START condition, the DAC8571 monitors the SDA bus, checking the device address being transmitted. Upon receiving the 10011A00 code, and the R/W bit, the DAC8571 outputs an acknowledge signal on the SDA line.

Broadcast addressing is also supported by DAC8571. Broadcast addressing can be used for synchronously updating or powering down multiple DAC8571 devices on the same bus. DAC8571 is designed to work with other members of DAC857x, DAC757x families to support multichannel synchronous update. When broadcast addressing is used, DAC8571 responds regardless of the state of the A0 pin. Broadcast address is only valid for write operation and cannot be used for read operation. Broadcast address is as follows.

| MSB | | | | | | LSB |
|-----|---|---|---|---|---|-----|
| 1 | 0 | 0 | 1 | 0 | 0 | 0 |

Control Byte

After transmitting an acknowledge pulse following a valid address, DAC8571 expects a control byte C<7:0>. Control byte functionality is shown in Table 5.

The first two MSBs C<7> and C<6> of the control byte must be zeroes for DAC8571 to update. If these two bits are not assigned to zero, DAC8571 ignores all update commands, but still generates an acknowledge signal.

C<5> and C<4> are used for setting the update mode. Some of these modes are designed to support multichannel synchronous operation between multiple devices.

- C<5>=0, C<4>=0: Store I²C data. The contents of MS byte and LS byte data (or power-down information) are stored into the temporary register. This mode does not change the DAC output.
- C<5>=0, C<4>=1: Update DAC with I²C data. Most common mode. The contents of MS byte and LS byte data (or power-down information) are stored into the temporary data register and into the DAC register. This mode changes the DAC output with the contents of I²C MS byte and LS byte data.

- C<5>=1, C<4>=0: Update with previously stored data. The contents of MS byte and LS byte data (or power-down information) are ignored. The DAC is updated with the contents of the data previously stored in the temporary register. This mode changes the DAC output.
- C<5>=1, C<4>=1: Broadcast update, If C<2>=0, DAC is updated with the contents of its temporary register. If C<2>=1, DAC is updated with I²C MS byte and LS byte data. C<7> and C<6> do not have to be zeroes in order for DAC8571 to update. This mode is intended to help DAC8571 work with other DAC857x and DAC757x devices for multichannel synchronous update applications.

C<3> should always be zero.

C<2> is utilized only when C<5>=C<4>=1. Otherwise, C<2> must be assigned to zero.

C<1> should always be zero.

C<0> should be zero during normal DAC operation. C<0>=1 is a power-down flag. If C<0>=1, M<7>, M<6>, and M<5> indicate a powerdown operation as shown in Table 6.

Table 5. Control Byte Functionality

| C<7> | C<6> | C<5> | C<4> | C<3> | C<2> | C<1> | C<0> | M<7> | M<6> | M<5> | DAC8571 FUNCTION |
|--------------------|------|-------|-------|------|--------|------|------|-------------|-------|-------------|---|
| | | Load1 | Load0 | | Brcsel | | PD0 | MSB | MSB-1 | MSB-2...LSB | |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | Data | | | Write temporary register with data |
| 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | See Table 6 | | | Write temporary register with power down command |
| 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | Data | | | Write temporary register and load DAC with data |
| 0 | 0 | 0 | 1 | 0 | 0 | 0 | 1 | See Table 6 | | | Power down DAC |
| 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | x | | | Update DAC with temporary register data or power down |
| Broadcast Commands | | | | | | | | | | | |
| x | x | 1 | 1 | x | 0 | x | x | x | | | Load all DACs, all devices with temporary register data |
| x | x | 1 | 1 | x | 1 | x | 0 | Data | | | Load all DACs, all devices with data |
| x | x | 1 | 1 | x | 1 | x | 1 | See Table 6 | | | Power down all DACs, all devices |

Most Significant Byte

Most Significant Byte M<7:0> consists of 8 most significant bits of D/A conversion data. When C<0>=1. M<7>, M<6>, M<5> indicate a powerdown operation as shown in Table 6.

Least Significant Byte

Least Significant Byte L<7:0> consists of the 8 least significant bits of D/A conversion data. DAC8571 updates at the falling edge of the acknowledge signal that follows the L<0> bit.

Data Transmit and Read-Back

I²C bus can be noisy and data integrity and can be a problem in a system of many I²C devices. To enable I²C system verification, DAC8571 provides read back capability for the user. During read back operation, the contents of the control byte, MS byte and the LS byte can be sent back to the master device using the I²C bus. This read-back function is also useful if a device on the I²C bus inquires DAC8571 data.

For read-back operation, the master device sends the I²C address and sets the R/W bit. DAC8571 acknowledges. Then, upon the receipt of clock pulses from the master, DAC8571 sends the MS byte. If the master acknowledges, DAC8571 sends the LS byte. If the master acknowledges, DAC8571 sends the control byte. This sequence is interrupted by the master sending a not acknowledge signal.

Depending on the contents of the control byte transmitted by the DAC8571, the MS byte and LS byte information (transmitted by the DAC8571) is interpreted as follows:

| C<5> | C<4> | C<2> | |
|------|------|------|---|
| 0 | 0 | 0 | MS and LS bytes represent temporary register data |

| C<5> | C<4> | C<2> | |
|------|------|------|---|
| 0 | 1 | 0 | MS and LS bytes represent temporary and DAC register data |
| 1 | 0 | 0 | MS and LS bytes represent I ² C data that is discarded |
| 1 | 1 | 0 | MS and LS bytes represent I ² C data that is discarded |
| 1 | 1 | 1 | MS and LS bytes represent temporary and DAC register data |

EXAMPLES (A0 TIED TO GND, VDD = 5 V)

| EXAMPLE 1: Write 1/4 scale to DAC8571 | | | | | | | | | |
|---|-----------------|-----|-----------|-----|-----------|-----|-----------|----------------|------|
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0000 | ACK | 0100 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = 1.25 V | |
| EXAMPLE 2: Switch DAC8571 to fast settling mode | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0001 | ACK | 0010 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = 0 V | |
| EXAMPLE 3: Switch DAC8571 back to low power mode | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0001 | ACK | 0000 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = 0 V | |
| EXAMPLE 4: Power-down DAC8571 with Hi-Z output | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0001 | ACK | 1100 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = Hi-Z | |
| EXAMPLE 5: Power-down DAC8571 with 1K output impedance to ground | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0001 | ACK | 0100 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = 0 V | |
| EXAMPLE 6: Power-down DAC8571 with 100K output impedance to ground | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0001 0001 | ACK | 1000 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = 0 V | |
| EXAMPLE 7: Store full scale data in temporary register | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0000 0000 | ACK | 1111 1111 | ACK | 1111 1111 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | | |
| EXAMPLE 8: Update DAC8571 with the data previously stored in the temporary register | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 1000 | ACK | 0010 0000 | ACK | XXXX XXXX | ACK | XXXX XXXX | ACK | STOP |
| Previous output voltage is valid | | | | | | | | New Vout valid | |
| EXAMPLE 9: Broadcast a powerdown command to all DAC8571s on the I²C bus | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 0000 | ACK | 0011 0101 | ACK | 1100 0000 | ACK | 0000 0000 | ACK | STOP |
| Previous output voltage is valid | | | | | | | | Vout = Hi-Z | |
| EXAMPLE 10: Broadcast update. All DAC8571s on the I²C bus update synchronously with the contents of their temporary registers | | | | | | | | | |
| | ADDRESS <7...0> | ACK | C<7...0> | ACK | M<7...0> | ACK | L<7...0> | ACK | STOP |
| START | 1001 0000 | ACK | 0011 0000 | ACK | XXXX XXXX | ACK | XXXX XXXX | ACK | STOP |
| Previous output voltage is valid | | | | | | | | New Vout valid | |

| | | | | | | | | | |
|---|-----------------------------|-------------------------|------------------------------|-------------------------|-----------------------|-------------------------|------------------------------|-------------------|------|
| EXAMPLE 11: Read back DAC8571 internal data. V denotes valid logic. | | | | | | | | | |
| START | ADDRESS<7...0> 1001 1001 | ACK | M<7...0> VVVV VVVV | MASTER ACK | L<7...0> VVVV VVVV | MASTER ACK | C<7...0> VVVV VVVV | MASTER NOT ACK | STOP |
| EXAMPLE 12: Ramp generation in high speed mode (up to code 7 is shown) | | | | | | | | | |
| START | HS Master Code 0000 1000 | NOT ACK | REPEATED START | ADDRESS 1001 1000 | ACK | C<7...0> 0001 0000 | ACK | | |
| Previous Vout voltage valid | | | Vout = 0 V | | | | Vout = 76 μ V | | |
| MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0000 | ACK | MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0001 | ACK | | |
| Previous Vout voltage valid | | | Vout = 2 \times 76 μ V | | | | Vout = 3 \times 76 μ V | | |
| MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0010 | ACK | MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0011 | ACK | | |
| Vout = 76 μ V | | | Vout = 4 \times 76 μ V | | | | Vout = 5 \times 76 μ V | | |
| MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0100 | ACK | MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0101 | ACK | | |
| Vout = 3 \times 76 μ V | | | Vout = 6 \times 76 μ V | | | | Vout = 7 \times 76 μ V | | |
| MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0110 | ACK | MSB<7...0> 0000 0000 | ACK | LSB<7...0> 0000 0111 | ACK | | |
| Vout = 5 \times 76 μ V | | | | | | | | | |

Power-On Reset

The DAC8571 contains a power-on-reset circuit that controls the output voltage during power-up. On power-up, the DAC register is filled with zeros and the output voltage is 0V; it remains there until a valid write sequence is made to the DAC. This is useful in applications where it is important to know the state of the output of the DAC while it is in the process of powering up. No input is brought high before the power is applied.

Power-Down Modes

The DAC8571 contains five separate power settings. These modes are programmable when C<0>=1. When C<0>=1, M<7>, M<6>, and M<5> bits represent power setting control bits, and M<4...0> and L<7...0> are assigned to zeroes. Power setting of DAC8571 is updated at the falling edge of the acknowledge signal that follows the least significant byte. To set the power consumption of the device, following I²C sequence is used.

| | |
|------------------------------|---------------------|
| Start_condition -> | |
| Valid_address | (1001 1000) -> ack |
| C<7:0> | (0001 0001) -> ack |
| M<7:0> | (vvv0 0000) -> ack |
| L<7:0> | (0000 0000) -> ack |
| Stop_condition | |

Table 6. Power Settings for the DAC8571 (C<0>=1)

| M<7> | M<6> | M<5> | Operating Mode |
|------|------|------|----------------------------|
| 0 | 0 | 0 | Low power mode, default |
| 0 | 0 | 1 | Fast settling mode |
| 0 | 1 | X | PWD. 1k Ω to GND |
| 1 | 0 | X | PWD. 100 k Ω to GND |
| 1 | 1 | X | PWD. Output Hi-Z |

After power-up, the device works in low power mode with its normal power consumption of 170 μA at 5 V. At fast settling mode, device consumes 250 μA nominally, but settles in 10 μs . For the three power-down modes, the supply current falls to 200 nA at 5 V (50 nA at 3 V). Not only does the supply current fall but the output stage is also internally switched from the output of the amplifier to a resistor network of known values. This has the advantage that the output impedance of the device is known while in power-down mode. There are three different options: The output is connected internally to GND through a 1-k Ω resistor, a 100-k Ω resistor or it is left open-circuit (high impedance). The output stage is illustrated in Figure 32.

A power on reset starts the DAC8571 in the low power mode. Low power mode and fast-settling mode settings stay unchanged during DAC8571 data updates, unless they are specifically overwritten as explained in Table 6. On the other hand, each new data sequence requiring a DAC update brings the DAC8571 out of the three power-down conditions.

DAC8571 power settings can be stored in the temporary register, just like data (use C<7:0> = 0000 0001). This allows simultaneous powerdown capability for multichannel applications.




Figure 32. Output Stage During Power-Down

All linear circuitry is shut down when the power-down mode is activated. However, the contents of the DAC register are unaffected when in power-down. The time to exit power-down is typically 2.5 μs for $V_{\text{DD}} = 5\text{ V}$ and 5 μs for $V_{\text{DD}} = 3\text{ V}$. (See the Typical Characteristics section for additional information.)

CURRENT CONSUMPTION

In the low power mode, the DAC8571 typically consumes 170 μA at $V_{\text{DD}} = 5\text{ V}$ and 150 μA at $V_{\text{DD}} = 3\text{ V}$ including reference current consumption. Fast settling mode adds 80 μA of current consumption, but ensures 10- μs settling. Additional current consumption can occur at the digital inputs if $V_{\text{IH}} \ll V_{\text{DD}}$. For most efficient power operation, CMOS logic levels are recommended at the digital inputs to the DAC. In power-down mode, typical current consumption is 200 nA.

DRIVING RESISTIVE AND CAPACITIVE LOADS

The DAC8571 output stage is capable of driving loads of up to 1000 pF while remaining stable. Within the offset and gain error margins, the DAC8571 can operate rail-to-rail when driving a capacitive load. Resistive loads of 2 k Ω can be driven by the DAC8571 while achieving a very good load regulation. Load regulation error increases when the DAC output voltage is close to supply rails. When the outputs of the DAC are driven to the positive rail under resistive loading, the PMOS transistor of each Class-AB output stage can enter into the linear region. When this occurs, the added IR voltage drop deteriorates the linearity performance of the DAC. This only occurs within approximately the top 20 mV of the DAC's digital input-to-voltage output transfer characteristic. The reference voltage applied to the DAC8571 may be reduced below the supply voltage applied to VDD in order to eliminate this condition if good linearity is a requirement at full scale (under resistive loading conditions).

AC PERFORMANCE

DAC8571 can achieve typical ac performance of 96-dB signal-to-noise ratio (SNR) and 65-dB total harmonic distortion (THD), making the DAC8571 a solid choice for applications requiring low SNR at output frequencies at or below 4 kHz.

OUTPUT VOLTAGE STABILITY

The DAC8571 exhibits excellent temperature stability of 5 ppm/°C typical output voltage drift over the specified temperature range of the device. This enables the output voltage of each channel to stay within a $\pm 25 \mu\text{V}$ window for a $\pm 1^\circ\text{C}$ ambient temperature change. Good power supply rejection ratio (PSRR) performance reduces supply noise present on V_{DD} from appearing at the outputs to well below $10 \mu\text{V}$. Combined with good dc noise performance and true 16-bit differential linearity, the DAC8571 becomes a perfect choice for closed-loop control applications.

SETTLING TIME AND OUTPUT GLITCH PERFORMANCE

Settling time to within the 16-bit accurate range of the DAC8571 is achievable within $10 \mu\text{s}$ for a full-scale code change at the input. Worst case settling times between consecutive code changes is typically less than $2 \mu\text{s}$, therefore, the update rate is limited by the I²C interface for digital input signals changing code-to-code. For full-scale output swings, the output stage of each DAC8571 channel typically exhibits less than 100-mV overshoot and undershoot when driving a 200-pF capacitive load. Code-to-code change glitches are extremely low ($\sim 10 \mu\text{V}$) given that the code-to-code transition does not cross an $N \times 4096$ code boundary. Due to internal segmentation of the DAC8571, code-to-code glitches occur at each crossing of an $N \times 4096$ code boundary. These glitches can approach 100 mVs for $N = 15$, but settle out within $\sim 2 \mu\text{s}$.

USING REF02 AS A POWER SUPPLY FOR DAC8571

Due to the extremely low supply current required by the DAC8571, a possible configuration is to use a REF02 5-V precision voltage reference to supply the required voltage to the DAC8571's supply input as well as the reference input, as shown in Figure 33. This is especially useful if the power supply is quite noisy or if the system supply voltages are at some value other than 5 V. The REF02 outputs a steady supply voltage for the DAC8571. If the REF02 is used, the current it needs to supply to the DAC8571 is $160\text{-}\mu\text{A}$ typical and $225\text{-}\mu\text{A}$ max for $V_{\text{DD}} = 5 \text{ V}$. When a DAC output is loaded, the REF02 also needs to supply the current to the load. The total typical current required (with a 5-k Ω load on a given DAC output) is:




Figure 33. REF02 as a Power Supply

$$160 \mu\text{A} + \frac{5 \text{ V}}{5 \text{ k}\Omega} = 1.16 \text{ mA}$$

The load regulation of the REF02 is typically 0.005%/mA, which results in an error of $290 \mu\text{V}$ for a 1.16-mA current drawn. This corresponds to a 3.82 LSB error for a 0-V to 5-V output range.

LAYOUT

A precision analog component requires careful layout, adequate bypassing, and clean, well-regulated power supplies.

The power applied to V_{DD} and V_{REF} should be well regulated and low noise. Switching power supplies and dc/dc converters often has high-frequency glitches or spikes riding on the output voltage. In addition, digital components can create similar high-frequency spikes as their internal logic switches states. This noise easily couples into the DAC output voltage through various paths between the power connections and analog output.

As with the GND connection, V_{DD} is connected to a +5-V power supply plane or trace that is separate from the connection for digital logic until they are connected at the power entry point. In addition, the 1- μ F to 10- μ F, and 0.1- μ F bypass capacitors are strongly recommended. In some situations, additional bypassing may be required, such as a 100- μ F electrolytic capacitor or even a Pi filter made up of inductors and capacitors—all designed to essentially lowpass filter the 5-V supply, removing the high frequency noise.

PACKAGING INFORMATION

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish | MSL Peak Temp ⁽³⁾ |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| DAC8571IDGK | ACTIVE | MSOP | DGK | 8 | 80 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR |
| DAC8571IDGKG4 | ACTIVE | MSOP | DGK | 8 | 80 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR |
| DAC8571IDGKR | ACTIVE | MSOP | DGK | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR |
| DAC8571IDGKRG4 | ACTIVE | MSOP | DGK | 8 | 2500 | Green (RoHS & no Sb/Br) | CU NIPDAU | Level-2-260C-1 YEAR |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION



QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| DAC8571IDGKR | MSOP | DGK | 8 | 2500 | 330.0 | 12.4 | 5.3 | 3.4 | 1.4 | 8.0 | 12.0 | Q1 |

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

| Device | Package Type | Package Drawing | Pins | SPQ | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| DAC8571IDGKR | MSOP | DGK | 8 | 2500 | 346.0 | 346.0 | 29.0 |

DGK (S-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE



4073329/E 05/06

- NOTES:
- A. All linear dimensions are in millimeters.
 - B. This drawing is subject to change without notice.
 - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 per end.
 - D. Body width does not include interlead flash. Interlead flash shall not exceed 0.50 per side.
 - E. Falls within JEDEC MO-187 variation AA, except interlead flash.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

TI products are not authorized for use in safety-critical applications (such as life support) where a failure of the TI product would reasonably be expected to cause severe personal injury or death, unless officers of the parties have executed an agreement specifically governing such use. Buyers represent that they have all necessary expertise in the safety and regulatory ramifications of their applications, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of TI products in such safety-critical applications, notwithstanding any applications-related information or support that may be provided by TI. Further, Buyers must fully indemnify TI and its representatives against any damages arising out of the use of TI products in such safety-critical applications.

TI products are neither designed nor intended for use in military/aerospace applications or environments unless the TI products are specifically designated by TI as military-grade or "enhanced plastic." Only products designated by TI as military-grade meet military specifications. Buyers acknowledge and agree that any such use of TI products which TI has not designated as military-grade is solely at the Buyer's risk, and that they are solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI products are neither designed nor intended for use in automotive applications or environments unless the specific TI products are designated by TI as compliant with ISO/TS 16949 requirements. Buyers acknowledge and agree that, if they use any non-designated products in automotive applications, TI will not be responsible for any failure to meet such requirements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products

| | |
|-----------------------------|--|
| Amplifiers | amplifier.ti.com |
| Data Converters | dataconverter.ti.com |
| DSP | dsp.ti.com |
| Clocks and Timers | www.ti.com/clocks |
| Interface | interface.ti.com |
| Logic | logic.ti.com |
| Power Mgmt | power.ti.com |
| Microcontrollers | microcontroller.ti.com |
| RFID | www.ti-rfid.com |
| RF/IF and ZigBee® Solutions | www.ti.com/lprf |

Applications

| | |
|--------------------|--|
| Audio | www.ti.com/audio |
| Automotive | www.ti.com/automotive |
| Broadband | www.ti.com/broadband |
| Digital Control | www.ti.com/digitalcontrol |
| Medical | www.ti.com/medical |
| Military | www.ti.com/military |
| Optical Networking | www.ti.com/opticalnetwork |
| Security | www.ti.com/security |
| Telephony | www.ti.com/telephony |
| Video & Imaging | www.ti.com/video |
| Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2008, Texas Instruments Incorporated