



FEATURES

- 20 WATTS MAXIMUM OUTPUT POWER
- OUTPUT CURRENT UP TO 6A
- STANDARD 2" X 1" X 0.4" PACKAGE
- HIGH EFFICIENCY UP TO 89%
- 2:1 WIDE INPUT VOLTAGE RANGE
- SIX-SIDED CONTINUOUS SHIELD
- FIXED SWITCHING FREQUENCY
- CE MARK MEETS 2006/95/EC, 93/68/EEC AND 2004/108/EC
- UL60950-1, EN60950-1 AND IEC60950-1 LICENSED
- ISO9001 CERTIFIED MANUFACTURING FACILITIES
- COMPLIANT TO RoHS EU DIRECTIVE 2002/95/EC

APPLICATIONS

Wireless Network
Telecom/Datacom
Industry Control System
Measurement
Semiconductor Equipment

OPTIONS

Negative logic Remote On/Off

DESCRIPTION

The FED20 series offer 20 watts of output power from a 2 x 1 x 0.4 inch package. The FED20 series with 2:1 wide input voltage of 9-18, 18-36 and 36-75VDC and features 1600VDC of isolation, short-circuit and over-voltage protection.

TECHNICAL SPECIFICATION

All specifications are typical at nominal input, full load and 25°C otherwise noted

OUTPUT SPECIFICATIONS		
Output power		20 Watts max
Voltage accuracy	Full load and nominal Vin	± 1%
Minimum load		0%
Voltage adjustability	Single output	± 10%
Line regulation	LL to HL at Full Load	± 0.2%
Load regulation	No Load to Full Load	± 0.5%
Cross regulation (Dual)	Asymmetrical load 25% / 100% FL	± 5%
Ripple and noise	20MHz bandwidth (Measured with a 0.1uF/50V MLCC)	See table
Temperature coefficient		±0.02% / °C, max
Transient response recovery time	25% load step change	250uS
Over voltage protection Zener diode clamp	1.5V output	3.9V
	1.8V output	3.9V
	2.5V output	3.9V
	3.3V output	3.9V
	5V output	6.2V
	12V output	15V
	15V output	18V
Over load protection	% of FL at nominal input	150% max
Short circuit protection	Hiccup, automatics recovery	
GENERAL SPECIFICATIONS		
Efficiency	See table	
Isolation voltage	Input to Output Input(Output) to case	1600VDC, min 1600VDC, min
Isolation resistance	10 ⁹ ohms, min	
Isolation capacitance	1000pF, max	
Switching frequency	500KHZ, typ	
Approvals and standard	IEC60950-1, UL60950-1, EN60950-1	
Case material	Nickel-coated copper	
Base material	Non-conductive black plastic	
Potting material	Epoxy (UL94-V0)	
Dimensions	2.00 X 1.00 X 0.40 Inch (50.8 X 25.4 X 10.2 mm)	
Weight	27g (0.95oz)	
MTBF (Note 1)	BELLCORE TR-NWT-000332	1.791 x 10 ⁶ hrs
	MIL-HDBK-217F	6.842 x 10 ⁵ hrs





INPUT SPECIFICATIONS			
Input voltage range	12V nominal input	9 – 18VDC	
	24V nominal input	18 – 36VDC	
	48V nominal input	36 – 75VDC	
Input filter	L-C type		
Input voltage variation	dv/dt	5V/ms,max (Complies with ETS300 132 part 4.4)	
Input surge voltage	12V input	36VDC	
	24V input	50VDC	
100mS max	48V input	100VDC	
	Input reflected ripple current	Nominal Vin and full load	20mA _{p-p}
Start up time	Nominal Vin and constant resistive load	Power up	10mS typ
		Remote ON/OFF	10mS typ
Remote ON/OFF (Note 6)	(Positive logic)(Standard)	DC-DC ON	Open or 3V < Vr < 12V
		DC-DC OFF	Short or 0V < Vr < 1.2V
(Negative logic)(Option)	DC-DC ON	Short or 0V < Vr < 1.2V	
	DC-DC OFF	Open or 3V < Vr < 12V	
Input current of remote control pin	Nominal Vin	-0.5mA ~ +0.5mA	
Remote off state input current	Nominal Vin	2.5mA	
ENVIRONMENTAL SPECIFICATIONS			
Operating temperature range	-40°C ~ +85°C (with derating)		
Maximum case temperature	100°C		
Storage temperature range	-55°C ~ +105°C		
Thermal impedance (Note 7)	Nature convection	12°C/Watt	
	Nature convection with heat-sink	10°C/Watt	
Thermal shock	MIL-STD-810F		
Vibration	10~55Hz, 10G, 30minutes along X,Y and Z		
Relative humidity	5% to 95% RH		
EMC CHARACTERISTICS			
EMI (Note 8)	EN55022	Class A	
ESD	EN61000-4-2	Air ± 8KV	
		Contact ± 6KV	
Radiated immunity	EN61000-4-3	10 V/m Perf. Criteria A	
Fast transient	EN61000-4-4	± 2KV Perf. Criteria B	
Surge (Note 9)	EN61000-4-5	± 1KV Perf. Criteria B	
Conducted immunity	EN61000-4-6	10 Vr.m.s Perf. Criteria A	




Model Number	Input Range	Output Voltage	Output Current		Output ⁽⁴⁾ Ripple & Noise	Input Current		Eff ⁽⁴⁾ (%)	Capacitor ⁽⁵⁾ Load max
			Min. load	Full load		No load ⁽³⁾	Full load ⁽²⁾		
FED20-12S1P5	9 – 18 VDC	1.5 VDC	0mA	6000mA	60mVp-p	70mA	1014mA	78	65000uF
FED20-12S1P8	9 – 18 VDC	1.8 VDC	0mA	6000mA	60mVp-p	75mA	1200mA	79	65000uF
FED20-12S2P5	9 – 18 VDC	2.5 VDC	0mA	6000mA	60mVp-p	80mA	1582mA	83	33000uF
FED20-12S3P3	9 – 18 VDC	3.3 VDC	0mA	5000mA	60mVp-p	115mA	1698mA	85	13000uF
FED20-12S05	9 – 18 VDC	5 VDC	0mA	4000mA	75mVp-p	75mA	2008mA	87	6800uF
FED20-12S12	9 – 18 VDC	12 VDC	0mA	1670mA	75mVp-p	90mA	2037mA	86	2200uF
FED20-12S15	9 – 18 VDC	15 VDC	0mA	1330mA	75mVp-p	35mA	2027mA	86	755uF
FED20-12D12	9 – 18 VDC	±12VDC	0mA	±833mA	100mVp-p	45mA	2032mA	86	±680uF
FED20-12D15	9 – 18 VDC	±15VDC	0mA	±667mA	100mVp-p	50mA	2034mA	86	±450uF
FED20-24S1P5	18 – 36 VDC	1.5 VDC	0mA	6000mA	60mVp-p	35mA	493mA	80	65000uF
FED20-24S1P8	18 – 36 VDC	1.8 VDC	0mA	6000mA	60mVp-p	45mA	584mA	81	65000uF
FED20-24S2P5	18 – 36 VDC	2.5 VDC	0mA	6000mA	60mVp-p	40mA	781mA	84	33000uF
FED20-24S3P3	18 – 36 VDC	3.3 VDC	0mA	5000mA	60mVp-p	30mA	838mA	86	13000uF
FED20-24S05	18 – 36 VDC	5 VDC	0mA	4000mA	75mVp-p	35mA	980mA	89	6800uF
FED20-24S12	18 – 36 VDC	12 VDC	0mA	1670mA	75mVp-p	55mA	1006mA	87	2200uF
FED20-24S15	18 – 36 VDC	15 VDC	0mA	1330mA	75mVp-p	40mA	1002mA	87	755uF
FED20-24D12	18 – 36 VDC	±12VDC	0mA	±833mA	100mVp-p	30mA	1004mA	87	±680uF
FED20-24D15	18 – 36 VDC	±15VDC	0mA	±667mA	100mVp-p	30mA	993mA	88	±450uF
FED20-48S1P5	36 – 75 VDC	1.5 VDC	0mA	6000mA	60mVp-p	15mA	247mA	80	65000uF
FED20-48S1P8	36 – 75 VDC	1.8 VDC	0mA	6000mA	60mVp-p	20mA	288mA	82	65000uF
FED20-48S2P5	36 – 75 VDC	2.5 VDC	0mA	6000mA	60mVp-p	30mA	391mA	84	33000uF
FED20-48S3P3	36 – 75 VDC	3.3 VDC	0mA	5000mA	60mVp-p	15mA	414mA	87	13000uF
FED20-48S05	36 – 75 VDC	5 VDC	0mA	4000mA	75mVp-p	20mA	490mA	89	6800uF
FED20-48S12	36 – 75 VDC	12 VDC	0mA	1670mA	75mVp-p	35mA	497mA	88	2200uF
FED20-48S15	36 – 75 VDC	15 VDC	0mA	1330mA	75mVp-p	50mA	501mA	87	755uF
FED20-48D12	36 – 75 VDC	±12VDC	0mA	±833mA	100mVp-p	20mA	496mA	88	±680uF
FED20-48D15	36 – 75 VDC	±15VDC	0mA	±667mA	100mVp-p	20mA	496mA	88	±450uF

Note



- BELLCORE TR-NWT-000332. Case 1: 50% Stress, Temperature at 40°C.
MIL-HDBK-217F Notice2 @Ta=25 °C, Full load(Ground, Benign, controlled environment).
- Maximum value at nominal input voltage and full load.
- Typical value at nominal input voltage and no load.
- Typical value at nominal input voltage and full load.
- Test by minimum Vin and constant resistive load.
- The ON/OFF control pin voltage is referenced to -Vin.
To order negative logic ON-OFF control add the suffix-N (Ex: FED20-24S05-N).
- Heat sink is optional and P/N: 7G-0020A.
- The FED20 series can meet EN55022 Class A with parallel an external capacitor to the input pins.
Recommend: 12Vin : 4.7µF/50V 1812 MLCC .
24Vin : 2.2µF/50V 1812 MLCC .
48Vin : 2.2µF/100V 1812 MLCC.
- An external filter capacitor is required if the module has to meet EN61000-4-5.
The filter capacitor Power Mate suggest: Nippon chemi-con KY series, 220 µF/100V, ESR 48mΩ.





1. All dimensions in Inches (mm)
Tolerance: X.XX±0.02 (X.X±0.5)
X.XXX±0.01 (X.XX±0.25)
2. Pin pitch tolerance ±0.01(0.25)
3. Pin dimension tolerance ±0.004 (0.1)


PIN CONNECTION		
PIN	SINGLE	DUAL
1	+ INPUT	+ INPUT
2	- INPUT	- INPUT
3	+ OUTPUT	+ OUTPUT
4	TRIM	COMMON
5	- OUTPUT	- OUTPUT
6	CTRL	CTRL



Recommended Filter for EN55022 Class B Compliance

The components used in the above figure, together with the manufacturers' part numbers for these components, are as follows:

	C1	C2	C3	C4	L1
FED20-12xxx	3.3uF/50V 1812 MLCC	3.3uF/50V 1812 MLCC	1000pF/2KV MLCC	1000pF/2KV MLCC	450uH Common Choke PMT-048
FED20-24xxx	4.7uF/50V 1812 MLCC	N/A	1000pF/2KV MLCC	1000pF/2KV MLCC	450uH Common Choke PMT-048
FED20-48xxx	2.2uF/100V 1812 MLCC	2.2uF/100V 1812 MLCC	1000pF/2KV MLCC	1000pF/2KV MLCC	325uH Common Choke PMT-050



Recommended EN55022 Class B Filter Circuit Layout